

IP Master Station

NNV-30



Features

10.2 inch screen, able to call, intercom, broadcast, with power supply, support calling, broadcasting, two-way video intercom, hosting, monitoring, support the shift nurse left a message or video, etc

Functions

Video intercom: support full duplex hd video intercom, including hands-free and handle two kinds of intercom.

Call forwarding: support for transferring call information to other hosts and time-sharing.

Broadcast: support all terminal equipment area, area, timing broadcast, broadcast Shouting, fire broadcast (need to purchase another fire matrix).

Access Control: support the door lock of ward to open and close, and can intercom with visitors visually to realize access control management.

Voice broadcast: support a variety of voice broadcast nursing level: support custom nursing level Settings.

Night mode: support night mode, custom setting night screen sleep time.

Audio and video recording: support audio and video recording (another 32GB audio and video module), can be viewed locally or on the server.

Photo message: this function allows the nurse to record the work that needs to be transferred locally for the view of the shift nurse.

Power supply: power supply by power adapter (DC14V/ 1.7a).

Technical Specifications

Network interface: standard RJ45 interface	Network protocol: TCP/IP, UDP, IGMP, RTP
Audio sampling rate: 16K ~ 48K Hz	Audio mode: 16 bit stereo CD sound quality
Broadcast audio format: MP3, WAV	Output frequency: 20 Hz ~ 20 k Hz
Harmonic distortion: < 0.5%	SNR: ≥ 90dB
Speaker power: 3W	MIC input sensitivity: 10mV
Audio stream: 16Kb ~ 192Kb	Recording output level (peak-to-peak) : < 3V
Audio input level (peak-to-peak) : < 1V	Camera: 5 megapixels
Video stream: 128Kb ~ 2Mb	Display resolution: 1280×800 pixels
External interface: rs-485 interface	Alarm outlet: DC14V 500mA(MAX)
Power consumption: < 7W	Operating temperature: -10°C ~ +60°C
Working humidity: 10% ~ 90%	Size: 208 x346x98mm [8.19x13.62x3.86in]
Microphone length: 320mm	